



Ordering Information

Part. No	Specifications								Application
	Pack Rate	Tx	Pout	Rx	S	Top	Reach	others	
RTXM192-550	SFP 2.5G	850nm VCSEL	-10 ~ -3dBm	PIN	< -18dBm	-10~70°C	300m	DDM, Note1	
RTXM192-400	SFP 2.5G	1310nm FP	-10 ~ -3dBm	PIN	< -18dBm	-10~70°C	2km	DDM, Note1	SDH I-16
RTXM192-450	SFP 2.5G	1310nm DFB	-5 ~ 0dBm	PIN	< -18dBm	-10~70°C	15km	DDM, Note1	SDH S-16.1
RTXM192-454	SFP 2.5G	1310nm DFB	-2 ~ +3dBm	PIN	< -20dBm	-10~70°C	30km	DDM, Note1	



RTXM192-xxx DDM

	CWDM		-28dBm		Note1		
RTXM192-859 SFP 2.5G	1591nm CWDM	0 ~ +3dBm APD	< -28dBm	0~70°C	80km	DDM, Note1	CWDM
RTXM192-861 SFP 2.5G	1611nm CWDM	0 ~ +3dBm APD	< -28dBm	0~70°C	80km	DDM, Note1	CWDM

WTD reserves the right to make changes to the product(s) or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

Edition 2009-12-1

Published by Wuhan Telecommunication Devices Co.,Ltd.

Copyright © WTD

All Rights Reserved.